



Second Nature Easy Mix Specifications

Product

Second Nature Easy Mix Mulch is made from a combination of post consumer recycled paper. It is non-toxic, biodegradable and contaminant-free.

Mixing Procedure

Mix Second Nature Easy Mix in up to 120 gallons of water to each 40-pound bag. When using a 30-pound bag reduce water to no more than 100 gallons per bag.

Add tackifiers as specified

Tank Time

Second Nature Easy Mix absorbs water quickly to become workable slurry. The slurry should appear as a blend with no separation in the mulch and water.

Application

Apply Second nature Easy Mix Mulch with seed and fertilizer added, or as a separate application after drilling or broadcasting. Good soil preparation is essential. Slurry containing seed and fertilizer is best applied from the hose by pointing the nozzle straight down to drive the material into the soil. The application should then be topped off by allowing the material to "rain on" the surface to achieve approximately a 85-90% coverage appearance.

Mix Ratio & Coverage Data

Mix ratio ----- 1 bag in up to
120 gallon of water
Minimum required usage 1,500 lbs. per acre

Appearance

Second Nature Easy Mix Mulch will appear dark green at the time of application. During the curing process, the color will gradually fade.

Equipment

Second nature Easy Mix Mulch is formulated for use in smaller jet-agitated hydroseeding machines.

Technical Assistance

Questions or requests for additional technical information should be addressed to: Technical Director, Central Fiber Corporation
800-654-6117.

Physical Properties

Recycled paper content (min)----- 90%
Moisture content ----- 12% (+/- 3%)
Ph @ 25C ----- 7% (+/- 1%)
Toxicity ----- non-toxic
Water holding capacity ----- 10x own weight.
Applied color ----- Green

Packaging & Shipping Data

Bag size ----- 17"x9"x26"
Bag wt ----- 30 or 40 lbs.
Pallet ----- 50 bags -- 93"Hx44"Wx53"D
Full truck ----- 22 pallets, 1100 bags

Manufacturer

Second Nature Easy Mix Mulch is manufactured by Central Fiber Corporation in Canton, Ohio 888-452-2630 and Wellsville, Kansas 800-654-6117.

Warranty

Central Fiber Corporation warrants that the properties of the product meet the specifications outlined in the latest product specification when installed in accordance with its application instructions. Hydroseeding contractors warrant their workmanship as outlined in their respective contract. Any liability will be limited to a refund or purchase price or replacement of material at manufacturer's option. Compliance with local codes and regulations and suitability of the product for any particular application is the responsibility of the installer and the property owner.