

Specifications

Product Name:	TOPCOAT® Alternative Daily Landfill Cover
Revision Date:	September 2011

1. Product Identification

TOPCOAT is an approved alternative daily landfill cover manufactured from virgin wood fiber and/or recycled paper, along with a proprietary binding agent and other performance-enhancing proprietary ingredients. It is non-toxic, biodegradable and contaminant-free.

2. Mixing

Mix TOPCOAT Alternative Daily Landfill Cover with approximately 100 gallons of water per 50 pound bag.

3. Application

TOPCOATs convenient one-bag system makes mixing a snap. With TOPCOAT there's no mixing time and no waiting to spray. It takes only about 20 minutes from start of mix to final cover for the working face of an average-sized landfill. TOPCOAT is fully effective as soon as it's applied.

Minimum Application Rate: 8 sq ft / Gallon of water. **Maximum Application Rate:** 10 sq ft / Gallon of water.

4. Equipment

TOPCOAT is mixed and applied with a standard hydroseeding machine. A mechanically agitated hydro seeding machine is recommended. Follow equipment manufacture's installation instructions and recommendations.

5. Product Composition / Property Values

Cellulose Fiber (<i>minimum</i>)	65% ($\pm 10\%$)
Proprietary Ingredients (<i>minimum</i>)	13% ($\pm 3\%$)
Moisture Content	13% ($\pm 3\%$)
Toxicity	non-toxic
Applied Color	Brown

6. Packaging and Shipping

Bag Dimensions, Net Weight	17"x 9"x 26", 50lbs
Pallet Dimensions, Quantity	75"H x 44"W x 53"D, 40 Bags
Full Truckload	22 pallets, 880 bags
Half Truckload	11 pallets, 440 bags

7. Technical Assistance

For additional technical information contact our Technical Department: (800) 654-6117.